



E-CLEAN(OAC)

Mineral derived
for inorganic soils

No petroleum derivatives.

characteristics

- 1、 For inorganic soils.
- 2、 For iron rust, scale, calcium, urine stone, etc.
- 3、 Applicable for removal of welding stains, post-production flux, and acid wash.



benefits

- (1) Improve safety by switching away from toxic products as sulfuric acid
- (2) Mitigation of damage to the metal, no effect on skin.

Packaging 1Lx20/5Lx4/20Lx1/D/M/IBC

Example

■ Rust ■ material : metal ■ concentration : pure ■ washing time : 20 min.



before



after

HOW TO USE	
Acid wash	5 ~ 30 minutes immersion. Warming the temperature is more effective for washing.
Iron powder removal	50 °C pure liquid / 1 ~ 30 minutes ultrasonic cleaning./ wash time depends on the degree of soil.
Rust removal	Removed by brushing after immerse or spray of pure liquid.

General data :

GENERAL	liquid	Water soluble
	pH	2.2~2.6
LAW	CSCL	Not applicable to PRTR
	FSA	Not applicable
	Labor law	Not applicable in organic law
SAFETY	biodegradability	N/D
	LD50 (oral)	5,000mg/kg
	LD50 (dermal)	5,000mg/kg



INFINITY ENTERPRISES, INC.

Takizawa Bldg.,

3-3-6 Ebisu, Shibuya-ku, Tokyo

150-0013 JAPAN

◀ For details please visit our website.
<https://www.safecare.jp>



Contact about the product is...